

3122 Sutton Boulevard Maplewood, MO 63143

www.brentwoodplastics.com

Phone: 314.968.1135

Fax: 314.968.4276

Safety Data Sheet

Section 1: Identification of the Substance/Mixture and the Company/Undertaking

1.1 Product Identifier

Product Name Low Density Polyethylene

Synonyms Ethene polymer; Ethylene Homopolymer; LDPE; Polyethylene

Product Grades All blown film grades

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified use(s) Plastic film, laminating, molding, coating.

1.3 Details of the supplier of the safety data sheet

Manufacturer Brentwood Plastics, Inc.

3122 Sutton Boulevard Maplewood, Missouri 63143

United States

www.brentwoodplastics.com

Telephone 314-968-1135

1.4 Emergency telephone number 800-466-1135

Section 2: Hazards Identification

EU/EEC

According to Regulation (EC) No 1272/2008 (CLP)/REACH 1907/2006 [amended by 453/2010] According to EU Directive 67/548/EEC (DSD) or 1999/45/EC (DPD)

2.1 Classification of the substance or mixture

CLP • Not classified • Not classified • Not classified

2.2 Label Elements

CLP Hazard • No label element(s) required

DSD/DPD Risk Phrases • No label element(s) required

2.3 Other Hazards

CLP • May form combustible dust concentrations in air.

According to Regulation (EC) No. 1272/2008 (CLP) this material is not considered hazardous.

• May form combustible dust concentrations in air.

According to European Directive 1999/45/EC this material is not considered dangerous.

United States (US)

According to OSHA 29 CFR 1910.1200 HCS

2.1 Classification of the substance or mixture
OSHA HCS 2012
• Not classified

2.2 Label Elements

OSHA HCS 2012 Hazard • No label element(s) required

statements

2.3 Other Hazards

• As shipped, product is not hazardous. Under United States Regulations (29 CFR 1910.1200 - Hazard Communication

Standard), this product is not considered hazardous.

Revision Date: 13/07/16 Page 1 of 7

Canada

According to WHMIS

2.1 Classification of the substance or mixture

WHMIS • Not classified

2.2 Label Elements

WHMIS • No label element(s) required

2.3 Other Hazards

• May form combustible dust concentrations in air.

In Canada, the product mentioned above is not considered hazardous under the Workplace Hazardous

Materials Information System (WHMIS).

Section 3: Composition/Information on Ingredients

3.1 Substances

• Material does not meet the criteria of a substance in accordance with Regulation (EC) No 1272/2008.

3.2 Mixtures

	Composition	
Chemical Name	Identifiers (CAS)	%
Polyethylene	9002-88-4	>99.9 - 97
Antioxidants* and/or Slip Reagant	Proprietary	,<0.75 - 0
Antiblock Reagant	Proprietary	<2 - 0

^{*} may contain Trisnonylphenylphosphite which under some fabrication conditions may form nonyl & octyl phenols.

Section 4: First Aid Measures

4.1 Description of first aid Measures

Inhalation

 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Give artificial respiration if victim is not breathing. If signs/symptoms continue, get medical attention.

Skin

• For thermal burns, flush or submerge effected area in cold water to dissipate heat. Cover with clean bandage material. Do not peel material from skin. Get medical attention. For contact at ambient temperatures, wash with soap and water.

Eyes

Ingestion

• If dust or molten material contacts with the eye, immediately flush with plenty of water for at least 15 minutes. If irritation persists, get medical attention immediately.

• First aid is not expected to be necessary if material is used under ordinary conditions and as

recommended.

4.2 Most important symptoms and effects, both acute and delayed

• Refer to Section 11 - Toxicological information.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to Physician

• Burns should be treated as thermal burns. The material will come off as healing occurs; therefore, immediate removal from the skin is not necessary.

Section 5: Firefighting Measures

5.1 Extinguishing media

Suitable Extinguishing Media Unsuitable Extinguishing Media

- Water, fog, dry chemical, foam, carbon dioxide.
- None known.

5.2 Special hazards arising from the substance or mixture

Unusual Fire and Explosion Hazards

• Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.

Hazardous Combustion Products **5.3 Advice for firefighters**

- Carbon dioxide, carbon monoxide, formaldehyde, acetaldehyde, irritating smoke.
- Wear positive pressure self-contained breathing apparatus (SCBA).
 Structural firefighters' protective clothing will only provide limited protection.

Revision Date: 13/07/16 Page 2 of 7

Section 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal Precautions

• Do not walk through spilled material. Do not breathe dust. Avoid contact with skin and eyes. Wear appropriate personal protective equipment, avoid direct contact.

Emergency Procedures

 Contain spill and monitor for excessive dust accumulation. Avoid unnecessary personnel and equipment traffic in the spill area. Ventilate closed spaces before entering.

6.2 Environmental Precautions

· No special environmental precautions necessary.

6.3 Methods and material for containment and cleaning up

Containment/Clean-up Measures

- · Avoid generating dust.
- Use clean nonsparking tools to collect material.
- Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration.

6.4 Reference to other sections

 Refer to Section 8 - Exposure Controls/Personal Protection and Section 13 -Disposal Considerations.

Section 7: Handling and Storage

7.1 Precautions for safe handling

Handling

- · Avoid contact with molten material; do not breathe fumes, vapors, dust or sprays from molten or burning material. When processing at > 600°F (315°C), consider use of a respirator to avoid breathing decomposition products.
- Do not use in areas without adequate ventilation. Minimize dust generation and accumulation. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations. Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres.
- · Use appropriate Personal Protective Equipment (PPE). Avoid contact with skin and eyes. Do not breathe dust. Wash thoroughly with soap and water after handling and before eating, drinking or using tobacco.

7.2 Conditions for safe storage, including any incompatibilities

Storage

· Keep container closed and in ventilated area, away from ignition sources, heat, open flames, and direct sunlight. Do not store with incompatible materials.

7.3 Specific end use(s)

• Refer to Section 1.2 - Relevant identified uses

7.4 Other Information

• For prevention of fire and explosion, keep from contact with incompatible materials. Minimize dust generation and accumulation. Because product may accumulate a static charge, use proper bonding and/or grounding procedures prior to transfer. In the United States of America, refer to NFPA® Pamphlet No. 654, "Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, 2006 edition."

Section 8: Exposure Controls/Personal Protection

8.1 Control parameters

Exposure Limits/Guidelines

• No applicable exposure limits available for product or components.

8.2 Exposure controls

Engineering Measures/Controls

· Good ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances; such as poorly ventilated spaces, very hot processing, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.

Personal Protective Equipment

Respiratory

· For limited exposure use an N95 dust mask. For prolonged exposure use an air-purifying respirator with high efficiency particulate air (HEPA) filters. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or symptoms are experienced.

Eye/Face

· Wear safety goggles.

Hands Skin/Body · Wear thermally resistant gloves and long sleeves when handling molten product. · Wear long sleeves and/or protective coveralls.

Environmental Exposure Controls

• Follow best practices for site management and disposal of waste.

Revision Date: 13/07/16 Page 3 of 7

Section 9: Physical and Chemical Properties

9.1 Information on Physical and Chemical Properties

Material Description

Physical Form	Solid	Appearance/Description	A translucent to whitish solid with an odorless to mild odor.
Color	Translucent to whitish.	Odor	Odorless to mild.
Odor Threshold	NDA		
General Properties			
Boiling Point	NDA	Melting Point	100 to 120° C(212 to 248°F)
Decomposition Temperature	>300° C (573° F) (estimated)	pH	NDA
Specific Gravity/Relative Density	0.901 to 0.935 Water=1	Water Solubility	Negligible
Viscosity	NDA	Explosive Properties	Not Explosive.
Oxidizing Properties	Not an oxidizer.		
Volatility		•	•
Vapor Pressure	NDA	Vapor Density	NDA
Evaporation Rate	NDA		
Flammability			
Flash Point	343° C (649° F) (estimated)	UEL	NDA
LEL	NDA	Autoignition	NDA
Flammability (solid, gas)	Not Flammable.		
Environmental	·	•	
Octanol/Water Partition coefficient	NDA		

9.2 Other Information

• No additional physical and chemical parameters noted.

Section 10: Stability and Reactivity

10.1 Reactivity

• No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

• Stable under normal temperatures and pressures.

10.3 Possibility of hazardous reactions

• Hazardous polymerization not indicated.

10.4 Conditions to avoid

• Heat, sparks, open flame.

10.5 Incompatible materials

• Strong oxidizing agents, fluorine.

10.6 Hazardous decomposition products

• No data available

Revision Date: 13/07/16 Page 4 of 7

Section 11: Toxological Information

11.1 Information on Toxological Effects

Component Name	CAS	Data
Polyethylene (97% to 100%)	9002-88-4	Acute Toxicity: orl-rat LD50:>8 gm/kg; ihl-rat LC50:75.5 gm/m3/30M
Antioxidant or Slip Reagant (0% TO 0.75%)	Proprietary	Acute Toxicity: Ingestion/Oral-rat LD50+>6000 mg/kg Irritation: Skin-Rat LD50+>2000 mg/kg
Antioxidant or Slip Reagant (0% TO 0.75%)	Proprietary	Acute Toxicity: oral-rat LD50•>600 mg/kg; skn-rbt LD50:>20 gm/kg;
Antioxidant or Slip Reagant (0% TO 0.75%)	Proprietary	Acute Toxicity: oral-rat LD50•>600 mg/kg; skn-rbt LD50:>20 gm/kg; Irritation: eye-rbt 500 mg MLD; eye-rbt 100 uL MLD

GHS Properties	Classification
Acute toxicity	EU/CLP•Acute Toxicity - Dermal - NDA; Acute Toxicity - Inhalation - Inconclusive data
	OSHA HCS 2012•Acute Toxicity - Dermal - NDA; Acute Toxicity - Inhalation - Inconclusive data
Aspiration Hazard	EU/CLP• Not relevant
	OSHA HCS 2012• Not relevant
Carcinogenicity EU/CLP• Classification criteria not met	
	OSHA HCS 2012 Classification criteria not met
Germ Cell Mutagenicity	EU/CLP• Classification criteria not met
	OSHA HCS 2012 Classification criteria not met
Skin corrosion/Irritation	EU/CLP• Classification criteria not met
	OSHA HCS 2012• Classification criteria not met
Skin sensitization	EU/CLP• Classification criteria not met
	OSHA HCS 2012• Classification criteria not met
STOT-RE	EU/CLP• NDA
	OSHA HCS 2012• NDA
STOT-SE	EU/CLP• NDA
	OSHA HCS 2012• NDA
Toxicity for Reproduction	EU/CLP• Classification criteria not met
	OSHA HCS 2012 Classification criteria not met
Respiratory sensitization	EU/CLP• Classification criteria not met
	OSHA HCS 2012 Classification criteria not met
Serious eye damage/Irritation	EU/CLP• Classification criteria not met
	OSHA HCS 2012• Classification criteria not met

Route(s) of entry/exposure Medical Conditions Aggravated by Exposure

- Inhalation, Skin, Eye, Ingestion
- · Disorders of the lungs.

Potential Health Effects

Inhalation Acute (Immediate)

- Exposure to dust may cause irritation. Processes such as cutting, grinding, crushing, or impact may result in generation of excessive amounts of airborne dusts in the workplace. Nuisance dust may affect the lungs but reactions are typically reversible.
- Prolonged exposure to the dust may cause wheezing, chest tightness, productive cough, nasal irritation and symptoms of chronic respiratory disease.

Acute (Immediate) Chronic (Delayed)

Chronic (Delayed)

- Exposure to dust may cause mechanical irritation.
- · No data available.

Eye

Skin

Acute (Immediate)
Chronic (Delayed)

- Exposure to dust may cause mechanical irritation. Excessive concentrations of nuisance dust in the workplace may reduce visibility and may cause unpleasant deposits in the eyes.
- No data available.

Ingestion

Acute (Immediate)
Chronic (Delayed)

- Excessive concentrations of nuisance dust in the workplace may cause mechanical irritation to the mucous membranes.
- No data available.

Key to abbreviations LD = Lethal Dose MLD = Mild

Revision Date: 13/07/16 Page 5 of 7

Section 12: Ecological Information

12.1 Toxicity

• NDA

12.2 Persistance and degradability

NDA

12.3 Bioaccumulative potential

• NDA

12.4 Mobility in Soil

• NDA

12.5 Results of PBT and vPvB assessment

• NDA

12.6 Other adverse effects

• NDA

Section 13: Disposal Considerations

13.1 Waste treatment methods

Product Waste Packaging Waste

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.
- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14: Transport Information

	14.1 UN number	14.2 UN proper shipping name	14.3 UN Transport hazard class(es)	14.4 Packing group	14.5 Environmental hazards
DOT	NDA	Not regulated	NDA	NDA	NDA
TGD	NDA	Not regulated	NDA	NDA	NDA
IMO/IMDG	NDA	Not regulated	NDA	NDA	NDA
IATA/ICAO	NDA	Not regulated	NDA	NDA	NDA

14.6 Special precautions for user

None known.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC

Not relevant.

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Hazard Classification

None

Inventories

• These products comply with the following inventories:

Australia AICS Canada DSL/NDSL China EU EINECS/ELNICS

Japan ENCS Korea KECL New Zealand Phillipines PICCS

USA TSCA

California Proposition 65 • In compliance, no reportable substances

CERCLA

• In the event of a spill, the end user should verify whether reporting is required under local, state, and/or

federal regulations.

CONEG• These products are in compliance with the heavy metals requirements of the Coalition of Northeastern

Governors and California Toxics in Packaging Prevention Act (AB2021).

Ozone Depleting Substances • In compliance with 40 CFR 82, no reportable substances.

RCRA

• In the form delivered by Brentwood Plastics, these products are not considered as hazardous waste

and are not subject to reporting under the Resource Conservation and Recovery Act.

15.2 Chemical Safety Assessment

· No chemical safety assessment has been carried out.

Revision Date: 13/07/16 Page 6 of 7

Section 16: Other Information

Last Revision Date

• 12/July/2016

For other information

Contact Brentwood Plastics, Inc. 1-800-466-1135

Disclaimer/Statement of Liability

• It is your responsibility to determine that our product is safe, lawful, and technically suitable for your intended uses. This safety data sheet cannot cover all possible situations which the user may experience during processing. Each aspect of the user's operation should be examined to determine if, or where, additional precautions may be necessary. All health and safety information contained in this safety data sheet should be provided to employees and/or customers. Brentwood Plastics, Inc must rely on the user to use this information to develop appropriate work practice guidelines and employee instructional programs specific to the user's operation.

As the conditions and methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of these products. Information contained herein is believed to be true and accurate, but all statements or suggestions are made without warranty, expressed, or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. Compliance with all applicable international, federal, state, and local laws and regulations regarding the use, storage, sale, transport or disposal of this material is the responsibility of the user

Brentwood Plastics, Inc. does not endorse or claim suitability of its product for any particular use. BRENTWOOD PLASTICS, INC MAKES NO WARRANTY OF MERCHANTABILITY AS TO ITS BLOWN FILM PRODUCTS. BRENTWOOD PLASTICS MAKES NO WARRANTIES, EXPRESS OR IMPLIED, CONCERNING THE SUITABILITY OR FITNESS OF ANY BRENTWOOD PLASTICS PRODUCT FOR ANY PARTICULAR USE. Brentwood Plastics' liability and your exclusive remedy for any claim arising out of the sales of its products are expressly limited at Brentwood Plastics' option to replacement of non-performing goods or payment not to exceed the purchase price plus transportation charges thereon in respect to any material which damage is proven and claimed.

The information in this sheet is valid for cited regulations published as of the date this document was prepared, as shown herein. Updates may be prepared as the regulations are amended or pending revised information about the resin. It is the customer's responsibility to seek updated regulatory information on any specific resin.

Key to abbreviations NDA = No data available

Revision Date: 13/07/16 Page 7 of 7